Preliminary Data Sheet

MS1310

Ultra-Low Jitter Temperature Compensated Crystal Oscillators (TCO)

Features

- Available at any frequency from 20 MHz to 2200 MHz
- Ultra-Low Jitter (12 KHz to 20 MHz)
  - 23.4 fs at 312.50 MHz
  - 21.5 fs at 491.52 MHz
  - 19.6 fs at 625 MHz
  - 21.7 fs at 1250 MHz
  - 18.8 fs at 1600 MHz
- Temperature stability of ±0.5ppm
- CML/LVDS/LVDS-EXT/LVPECL/HCSL output formats
- Output Enable/Disable Feature
- < 10 ms start-up time
- No activity dips or micro jumps
- Industry standard 3.2X2.5 mm 8-pin LGA package
- Single 1.8V supply with internal regulator
- Superior power supply immunity
- Temperature range: -40°C to 85°C
- Temperature extended range: -40°C to 105°C
- ESD HBM 2000V, CDM 500V
- Lead free / RoHS compliant

Applications

- Network Equipment (Optical Modules, routers)
- 100G/200G/400G/800G OTN, Coherent optics
- Storage, switches, servers, NICs, accelerators
- Datacenter
- 3G to 24G SDI broadcast video
- 10G/40G/100G optical ethernet
- 56G/112G PAM4 Clocking
- Test and measurement equipment



General Description

The MS1310 is a digitally synthesized temperature compensated crystal oscillator (TCO) that combines advanced Bulk Acoustic Wave (BAW) resonator technology with high-performance digital frequency synthesis to deliver highly stable, fully programmable multi-GHz clocks with extremely low phase Jitter.

Built-in Adaptive Intelligence continuously monitors operating conditions in the background, using autonomous DSP algorithms to maintain robust and consistent performance across process, voltaFigge, and temperature.

The devices are factory programmed to provide an accurate frequency between 20 MHz and 2200 MHz at less than 1 ppb resolution.

The MS1310 is manufactured in a high-volume 28 nm CMOS process and represents the most advanced node in the timing industry.

Device Information

Part Number	Package	Description
MS1310	3.2X2.5 mm 8-pin LGA	TCXO

Figure 1. Functional Block Diagram



MS1310

Pin Assignment and Pin Description



Figure 2. MS1310 Pin Assignments

Table 1. MS1310 Pin Descriptions

Pin No	Name	Description
1	NC	No Connect
2	OE	Output Enable • High/Floating: Output enabled (Internal pull-up of 100kΩ) • Low: Output disabled
3	GND	Ground
4	CLK+	Clock Output
5	CLK-	Complementary Clock Output
6	VDD	Power Supply – connect bypass capacitor between this pin and pin 3. Keep bypass as close as possible to the pins
7	NC	No Connect
8	NC	No Connect

Part Ordering Information

Figure 3 shows a logic tree for ordering each of the available parts.



Figure 3. MS1310 Part Ordering Information

Table 11. Example of ordering part number

Base P/N	Output Format	Operating Temperature	Frequency Code	Shipment Type	**Ordering part number**
MS1310	HCSL	-40°C to 85°C	491.52 MHz	Tape and Reel	**MS1310EA491M5200R**
MS1310	LVPECL	-40°C to 105°C	1250 MHz	Tape and Reel	**MS1310DB1250M000R**

Specifications

Table 2. Electrical Specifications

Typical values are specified at T_A= 25°C, V_{DD}=1.8V unless otherwise specified. All Min and Max limits are specified over the operating temperature range and voltage range with standard termination. A 0.1uF and 10uf bypass capacitor should be connected between VDD and GND pins located close to the device.

Parameter	Symbol	Test Condition/Comment	Min	Typ	Max	Unit
Frequency Range						
Frequency Range	F_{CLK}	All Output Formats	20		2200	MHz
Frequency Stability						
Frequency Stability (Temperature)	F_{TS}	-40°C to 85°C	-0.5		0.5	ppm
Frequency Stability (Temperature)	F_{TS}	-40°C to 105°C	-1		1	ppm
Frequency Tolerance	F_{INIT}	25°C±2°C, after 2x flow soldering	-1		+1	ppm
First Year Aging	F_1yr	25°C±2°C	-1		1	ppm
Clock Output Jitter Characteristics						
RMS Phase Jitter (12 KHz – 20 MHz)	Φ_{JITTER}	Frequency= 491.52 MHz		21.6	32	fs
		Frequency= 625 MHz		19.6	30	fs
Note: Phase jitter measured on Agilent 5052B Signal Source Analyzer						
Operating Voltage/Temperature Range						
Supply Voltage	V_{DD}		1.71	1.8	1.89	V
Temperature Range	T_A	Industrial Temperature	-40		85	°C
		Extended Industrial Temperature	-40		105	°C

Current Consumption

Supply Current	I_{DD}	LVDS Output (Output Enabled)		150	180	mA
		All Other Outputs (Output Enabled)		160	190	mA
		Tristate Hi-Z (Output Disabled)		70	84	mA

Input Characteristics

Digital Input Levels (OE)	V_{IH}		$0.7XV_{DD}$			V
	V_{IL}				$0.3XV_{DD}$	V
Output Enable (OE)	T_D	Output Disable Time			3	us
	T_E	Output Enable Time			20	us
Powerup Time	T_{PWR}	Time from 0.9xVDD until output frequency (F_{CLK}) within spec			10	ms

PSRR Characteristics

Power Supply-Induced Phase Noise	PSPN	Spurs induced by 50mV power supply ripples (312.5MHz)		-114		dBc
Power Supply-Jitter Sensitivity	PSJS			0.1		fs/mv

Note:

(1) Measured with 50 mVpp ripple from 50 KHz to 1 MHz applied on VDD Pin

Output Characteristics

Output Duty Cycle	DC	All Output Formats	48		52	%
Output Rise/Fall Time (20% to 80% V_{PP})	T_R / T_F	All Output Formats		50	70	ps
CML Output (AC-Coupled)	Vpp	Differential Pk-Pk See Figure 9, Figure 10	0.6	0.8	1	V
LVDS Output (AC-Coupled)	Vpp	Differential Pk-Pk See Figure 11	0.5	0.7	0.9	V
LVDS-EXT Output (AC-Coupled)	Vpp	Differential Pk-Pk See Figure 11	0.8	1.2	1.6	V
LVPECL Output (AC-Coupled)	Vpp	Differential Pk-Pk See Figure 12, Figure 13	1.2	1.4	1.6	V
HCSL Output (AC or DC-Coupled)	Vpp	Differential Pk-Pk See Figure 14, Figure 15	1.1	1.35	1.6	V
HCSL Output Voltage (DC- Coupled)	V_{CM}	Common Mode Voltage	340	350	360	mV

Table 3. Absolute Maximum Ratings

Parameter	Min	Max	Unit
1.8V Supply Voltage	-0.3	1.98	V
Digital I/O	-0.3	1.98	V
Maximum Operating Temperature		105	°C
Storage Temperature	-55	150	°C
Soldering Temperature		260	°C
Junction Temperature		150	°C
Note: Stresses that exceed what is listed in this table may cause permanent damage to the device. Exposure to conditions above the recommendations for extended periods of time may affect device reliability.			

Table 4. Environmental Compliance

Parameter	Test Condition
Mechanical Shock	MIL-STD-883, Method 2002
Mechanical Vibration	MIL-STD-883, Method 2007
Moisture Sensitivity Level (MSL)	3
Note: For additional information not listed, please contact Mixed-Signal Devices.	

Table 5. ESD Levels

Description	Description	Specification	Level
HBM[1]	Human Body Model	JEDEC JS-001	2000V
CDM[2]	Charge Device Model	JEDEC JESD22-C101	500V

Notes:
1. 1000V HBM allows safe manufacturing with standard ESD control process – JEDEC document JEP155
2. 250V CDM allows safe manufacturing with standard ESD control process – JEDEC document JEP157

Table 6. Package Thermal Information

Package	Parameter	Symbol	Value	Unit
3.2mmx2.5mm 8 pin LGA	Thermal Resistance, Junction to Ambient	$ø_{JA}$	80	°C/W
	Thermal Resistance, Junction to Board	$ø_{JB}$	40	°C/W
	Air Flow Condition		0	mps
	Maximum Junction Temperature	T_J	125	°C

Note: The thermal resistance information stated in this table is based on a standard JEDEC PCB condition. The actual thermal resistance varies depending on the customer PCB design.

Table 7. Typical Output Phase Noise Characteristics
VDD= 1.8V, T_A = 25°C, Output Type = LVDS-EXT

Offset frequency	312.5 MHz	491.52 MHz	625 MHz	1250 MHz	Unit
1 KHz	-103	-98	-99	-93	dBc/Hz
10 KHz	-132	-130	-127	-122	dBc/Hz
100 KHz	-154	-152	-149	-143	dBc/Hz
1 MHz	-164	-160	-159	-152	dBc/Hz
10 MHz	-165	-161	-160	-151	dBc/Hz
20 MHz	-166	-161	-160	-153	dBc/Hz
RMS Jitter (12 KHz – 20 MHz)	22	22	20	22	fs

Typical Output Measured Phase Noise Plots

This section shows MS1310 performance plots.

Measurement parameters are: VDD = 1.8 V, TA = 25°C, Output Type = LVDS-EXT.

The plots were captured using an Agilent E5052B Signal Source Analyzer.



Figure 4. Center Frequency: 312.5 MHz



Figure 5. Center Frequency: 491.52 MHz



Figure 6. Center Frequency: 625 MHz



Figure 7. Center Frequency: 1250 MHz

Output Terminations

Output Type	Differential Output Swing Vpp (Typ)	Coupling	Termination
CML	0.8V	AC	100 Ω diff
LVDS	0.7V	AC	100 Ω diff
LVDS-EXT	1.2V	AC	100 Ω diff
LVPECL	1.4V	AC	50 Ω to VT
LVPECL (DC Bias Resistor)	1.4V	AC	150 Ω to 250 Ω to GND, 50 Ω to VT
HCSL (Int Term)	1.35V	AC or DC	None
HCSL	1.35V	DC	50 Ω to GND



Figure 8. Differential Output Swing



Figure 9. AC-Coupled CML



Figure 10. AC-Coupled CML (Receiver Termination)



Figure 11. AC-Coupled LVDS



Figure 12. AC-Coupled LVPECL



Figure 13. AC-Coupled LVPECL (DC Bias Resistor)



Figure 14. HCSL (Integrated Termination)



Figure 15. DC-Coupled HCSL (Receiver Termination)

Output Timing



Figure 16. Output Timing across differential pair (CLK_P-CLK_N)



Figure 17. HCSL Output Level across differential pair (CLK_P-CLK_N)



Figure 18. Powerup Timing



Figure 19. OE Enable/Disable Timing

Packaging Information

Figure 20 shows the MS1310 packaging drawing.



Figure 20. MS1310 Packaging Drawing (3.2mm x 2.5 mm)

Table 8. MS1310 Packaging Dimensions

Dimensions	Min	Nom	Max
A		2.5 BSC	
B		3.2 BSC	
C	1.246	1.346	1.446
W	0.55	0.6	0.65
L	0.5	0.55	0.6
W1	0.35	0.4	0.45
L1	0.35	0.4	0.45
e		1.1 BSC	
D1		2.2 BSC	
Package Edge Tolerance		0.1	
Mold Flatness		0.1	
Coplanarity		0.08	

Note: All dimensions are in millimeters

Packaging Land Pattern

Figure 21 shows the MS1310 PCB land pattern.



Figure 21. MS1310 Packaging Land Pattern Drawing (3.2mm x 2.5mm)

Table 9. MS1310 Packaging Land Pattern Dimensions

Dimensions	In mm
L	0.7
W	0.7
L1	0.5
W1	0.55
E	1.1
F	2.6
G	1.76

Device Top Marking



Figure 22. MS1310 Device Top Marking Showing Pin 1

Table 10. MS1310 Device Marking Legend

Line	Position	Description
1	1	Product Marking
2	1-5	Lot Number
	6-7	Wafer Number
3	Lot Trace Code	
	1	Pin 1 Orientation Mark (Dot)
	2-3	Year (last two digits of the year)
	4-5	Calendar Work Week Number (1-53)
	7-8	Assembly Code

Reflow Profile (IPC/JEDEC-STD-020)

Figure 23 shows the reflow profile for MS1310



Figure 23. MS1310 Reflow Profile

IMPORTANT NOTICE AND DISCLAIMER

MIXED-SIGNAL DEVICES INC. PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES “AS IS” AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD-PARTY INTELLECTUAL PROPERTY RIGHTS.

Mailing Address: Mixed-Signal Devices Inc, 2 Venture, Suite 300, Irvine, California 92618, USA Copyright © 2026.